

These 12 volt fully dimmable magnetic power supplies meet or exceed all UL Standards 2108 and 1838, CUL, ANSI/UL, CSA requirements.

OUTPUT VOLTAGE - 12VDC, CLASS 2

PROTECTION - Standard with secondary protection. (See chart below)

DIMMABLE - 120 Volt: Lutron Maestro dimmer MRF2-6ND-120
Legrand Wattstopper HDA-703
277 Volt: Lutron Nova T dimmer NTLV-600-277

CASE - Suitable for indoor or outdoor locations.
20 gauge steel powdercoat *NEMA 3R* case.

KNOCKOUTS - Two 7/8" diameter knockouts on bottom of case, used for conduit fittings.

WARRANTY - 5 years after date of purchase.

LISTINGS - E.T.L. Listed.

Made in the U.S.A.



Output VDC	Watts	Input VAC	Breakers	Frequency	Dimensions LxWxH	Weight	DRIVER
12	24	120	1x2A	60 Hz	8.5" x 3.625" x 2.25"	3.5 lbs	DSH-DR24-12V-MAG
12	24	277	1x2A	60 Hz	8.5" x 3.625" x 2.25"	3.5 lbs	DSH-DR24-12V-MAG-277
12	60	120	1x5A	60 Hz	8.5" x 3.625" x 3"	4.5 lbs	DSH-DR60-12V-MAG
12	60	277	1x5A	60 Hz	8.5" x 3.625" x 3"	4.5 lbs	DSH-DR60-12V-MAG-277
12	96	120	2x4A	60 Hz	8.5" x 3.625" x 3"	4.5 lbs	DSH-DR96-12V-MAG
12	96	277	2x4A	60 Hz	8.5" x 3.625" x 3"	4.5 lbs	DSH-DR96-12V-MAG-277