

These 24 volt fully dimmable magnetic power supplies meet or exceed all UL Standards 2108 and 1838, CUL, ANSI/UL, CSA requirements.

OUTPUT VOLTAGE - 24VDC, CLASS 2

PROTECTION - Standard with secondary protection. (See chart below)

DIMMABLE - 120 Volt: Lutron Maestro dimmer MRF2-6ND-120
Legrand Wattstopper HDA-703
277 Volt: Lutron Nova T dimmer NTLV-600-277

CASE - Suitable for indoor or outdoor locations.
20 gauge steel powdercoat *NEMA 3R* case.

KNOCKOUTS - Two 7/8" diameter knockouts on bottom of case, used for conduit fittings.

WARRANTY - 5 years after date of purchase.

LISTINGS - E.T.L. Listed.

Made in the U.S.A.



14.25" L x 8.5" W x 5" D

Output VDC	Watts	Input VAC	Breakers	Frequency	Dimensions LxWxH	Weight	DRIVER
24	192	120	2x4A	60 Hz	14.25" x 8.5" x 5"	14 lbs	DSH-DR192-24V-MAG
24	192	277	2x4A	60 Hz	14.25" x 8.5" x 5"	14 lbs	DSH-DR192-24V-MAG-277
24	288	120	3x4A	60 Hz	14.25" x 8.5" x 5"	20 lbs	DSH-DR288-24V-MAG
24	288	277	3x4A	60 Hz	14.25" x 8.5" x 5"	20 lbs	DSH-DR288-24V-MAG-277
24	384	120	4x4A	60 Hz	14.25" x 8.5" x 5"	22 lbs	DSH-DR384-24V-MAG
24	384	277	4x4A	60 Hz	14.25" x 8.5" x 5"	22 lbs	DSH-DR384-24V-MAG-277