

SPOOL DIMENSIONS - (W) 0.41" x (H) 0.20" x (L) 32.8 ft. (10m)

MAXIMUM RUN - 32.8 feet

WATTAGE - 1.44 watts/ft.

VOLTAGE - 24VDC

LAMPS - LED SMD 3528, 300 LED's per 10m spool.
Spaced at 1.25" on center. CRI 90+

FIELD CUTTABLE - Every 4 inches.

BEAM ANGLE - 120 degrees.

LUMEN OUTPUT - 110 lumens/ft.

COLOR - White (2700K, 3000K, 4000K, 6000K).



Colors (Special Order) - White 2400K, Red, Green, Blue, Amber.

LIFE HOURS - 60,000 hours.

ELECTRICAL - Flexible circuit board ribbon. Additional aluminium heat sink may be required.

MOUNTING OPTIONS - Pre-applied 3M adhesive tape, mounting clips, and polycarbonate channels. Should custom requirements be necessary, please contact your local rep.

WARRANTY - 5 years from date of purchase.

CRI - 90+ **LISTINGS** -  Listed (E166352 IFDR) (E 348777),  approved.



ORDERING INFORMATION

| CATALOG # | DESCRIPTION | LED COLOR |
|--------------------|---------------------|-------------------------------|
| DSHWL-1370-24V-W24 | DSHWL-1370-24V-W24 | White (2400K) (SPECIAL ORDER) |
| DSHWL-1370-24V-W27 | DSHWL-1370-24V-W27 | White (2700K) |
| DSHWL-1370-24V-W31 | DSHWL-1370-24V-W31 | White (3100K) |
| DSHWL-1370-24V-W40 | DSHWL-1370-24V-W40 | White (4000K) |
| DSHWL-1370-24V-W60 | DSHWL-1370-24V--W60 | White (6000K) |
| DSHWL-1370-24V-RD | DSHWL-1370-24V-RD | Red (SPECIAL ORDER) |
| DSHWL-1370-24V-GN | DSHWL-1370-24V-GN | Green (SPECIAL ORDER) |
| DSHWL-1370-24V-BL | DSHWL-1370-24V-BL | Blue (SPECIAL ORDER) |
| DSHWL-1370-24V-AM | DSHWL-1370-24V-AM | Amber (SPECIAL ORDER) |