

SPOOL DIMENSIONS - (W) 0.32" x (H) 0.080" x (L) 16.4 ft. (5m)

MAXIMUM RUN - 16.4 feet (5m)

WATTAGE - 3.9 watts/ft.

VOLTAGE - 24VDC

LAMPS - LED SMD 2835, 126 LED's per meter. Spaced at 0.312" on center.

FIELD CUTTABLE - Every 2.19" inches.

BEAM ANGLE - 120 degrees.

LUMEN OUTPUT - 470 lumens/ft.



COLORS - White (2400K), White (2700K), White (3100K), White (4000K), White (6000K), Red, Green, Blue and Amber.

LIFE HOURS - 60,000 hours.

ELECTRICAL - Flexible circuit board ribbon. Additional aluminium heat sink may be required.

MOUNTING OPTIONS - Pre-applied 3M adhesive tape, mounting clips, and polycarbonate channels. Should custom requirements be necessary, please contact your local rep.

WARRANTY - 5 years from date of purchase.

CRI - 90+ **LISTING** -  Listed (E166352 IFDR) (E 348777),  approved.



Polymer encased for IP65 applications.

ORDERING INFORMATION

CATALOG #	DESCRIPTION	LED COLOR
DSHWL-4.0-24V-W24	DSHWL-4.0-24V-W24	White (2400K) (SPECIAL ORDER)
DSHWL-4.0-24V-W27	DSHWL-4.0-24V-W27	White (2700K)
DSHWL-4.0-24V-W31	DSHWL-4.0-24V-W31	White (3100K)
DSHWL-4.0-24V-W40	DSHWL-4.0-24V-W40	White (4000K)
DSHWL-4.0-24V-W60	DSHWL-4.0-24V-W60	White (6000K) (SPECIAL ORDER)
DSHWL-4.0-24V-RD	DSHWL-4.0-24V-RD	Red (SPECIAL ORDER)
DSHWL-4.0-24V-GN	DSHWL-4.0-24V-GN	Green (SPECIAL ORDER)
DSHWL-4.0-24V-BL	DSHWL-4.0-24V-BL	Blue (SPECIAL ORDER)
DSHWL-4.0-24V-AM	DSHWL-4.0-24V-AM	Amber (SPECIAL ORDER)