

**SPOOL DIMENSIONS** - (W) 0.275" x (H) 0.080" x (L) 32.8 ft. (10m)

**MAXIMUM RUN** - 32.8 feet

**WATTAGE** - 2.2 watts/ft.

**VOLTAGE** - 24VDC

**LAMPS** - LED SMD 2835, 60 LED's per meter.  
Spaced at 0.625" on center. CRI 90+

**FIELD CUTTABLE** - Every 4 inches.

**BEAM ANGLE** - 120 degrees.

**LUMEN OUTPUT** - 246 lumens/ft.

**COLOR** - White (2700K, 3100K, 3500K, 4000K, 6000K).


Colors (Special Order) - White 2400K, Red, Green, Blue, Amber.

**LIFE HOURS** - 60,000 hours.

**ELECTRICAL** - Flexible circuit board ribbon. Additional aluminium heat sink may be required.

**MOUNTING OPTIONS** - Pre-applied 3M adhesive tape, mounting clips, and polycarbonate channels. Should custom requirements be necessary, please contact your local rep.

**WARRANTY** - 5 years from date of purchase.

**CRI** - 90+    **LISTINGS** -  Listed (E166352 IFDR) (E 348777),  approved.



Polymer encased for IP65 applications.

## ORDERING INFORMATION

CATALOG #	DESCRIPTION	LED COLOR
DSHWL-2.2-24V-W24	DSHWL-2.2-24V-W24	White (2400K) (SPECIAL ORDER)
DSHWL-2.2-24V-W27	DSHWL-2.2-24V-W27	White (2700K)
DSHWL-2.2-24V-W31	DSHWL-2.2-24V-W31	White (3100K)
DSHWL-2.2-24V-W35	DSHWL-2.2-24V-W35	White (3500K) (SPECIAL ORDER)
DSHWL-2.2-24V-W40	DSHWL-2.2-24V-W40	White (4000K)
DSHWL-2.2-24V-W60	DSHWL-2.2-24V-W60	White (6000K) (SPECIAL ORDER)
DSHWL-2.2-24V-RD	DSHWL-2.2-24V-RD	Red (SPECIAL ORDER)
DSHWL-2.2-24V-GN	DSHWL-2.2-24V-GN	Green (SPECIAL ORDER)
DSHWL-2.2-24V-BL	DSHWL-2.2-24V-BL	Blue (SPECIAL ORDER)
DSHWL-2.2-24V-AM	DSHWL-2.2-24V-AM	Amber (SPECIAL ORDER)