

WATTAGE - 20 watts to 96 watts available.

INPUT VOLTAGE - 120VAC to 277VAC available.

OUTPUT VOLTAGE - 12VDC and 24VDC available.

PROTECTION - Short circuit / Over current / Over voltage

CASE - 20 gauge CRS powdercoat and KO's on both ends.

WARRANTY - 5 years from date of purchase.

LISTINGS - U.L. listed.



Constant voltage LED drivers.

Triac supports forward and reverse phase dimming.



Output VDC	Watts	Input VAC	Non-Dim	0-10 Dim	ELV Dim	Triac Dim	Dimensions LxWxH	DRIVER
12	20	100-240	✓				9.5" x 2.2" x 1.5"	DSH-1114-1220
12	35	100-240	✓				9.5" x 2.2" x 1.5"	DSH-1114-1235
12	60	100-240	✓				12.25" x 2.2" x 1.5"	DSH-1115-1260
12	60	120-277		✓			12.25" x 2.2" x 1.5"	DSH-1115-1260-DIM
24	20	100-240	✓				9.5" x 2.2" x 1.5"	DSH-1114-2420
24	35	100-240	✓				9.5" x 2.2" x 1.5"	DSH-1114-2435
24	60	100-240	✓				12.25" x 2.2" x 1.5"	DSH-1115-2460
24	96	120-277	✓				12.25" x 2.2" x 1.5"	DSH-1115-2496
24	96	120-277		✓			12.25" x 2.2" x 1.5"	DSH-1115-2496-DIM
24	40	120-277		✓	✓	✓	9.25" x 3.375" x 2"	DSH-1118-2440-DIM
24	60	120-277		✓	✓	✓	9.25" x 3.375" x 2"	DSH-1118-2460-DIM
24	96	120-277		✓	✓	✓	9.25" x 3.375" x 2"	DSH-1118-2496-DIM